



Batten Bars

PRODUCT DATA SPECIFICATIONS

PRODUCT DESCRIPTION

OMG's Batten Bars are designed to secure single-ply membrane to steel, wood, concrete, gypsum and other cementitious decks. Use the appropriate OMG fastener for the specific substrate.

OMG's Standard Bar is made of Galvalume.[®] The Polymer Batten Bar, is a modified polymer. For Galvalume bars, all ends have been rounded and edges have been deburred. Holes are punched into each bar with standard spacing of 1 6-in. or 12-in. (150 or 300 mm) on center. Polymer Batten Bar is punched 3-in. (75 mm) on center only. Galvalume batten bars are also available with custom hole spacing.

APPLICATION

Standard Bar: For use on steel, wood and concrete decks.

Polymer Batten Bar: For attaching single-ply membrane to steel, wood and structural concrete roof decks.

PACKAGING

Galvalume Bars: Galvalume batten bars come in 10-ft. (3 m) lengths, and are packaged in tubes of 50 (500-ft. [152.5 m] total). There are 10 tubes/pallet or 5,000-ft. (1525 m).

Polymer Bar: Packaged in 250-ft. (76.25 m) coils and supplied in a "pizza" style box.

Factory Mutual listings refer to Polymer Batten Bar as Polymer Batten Strip.



USE WITH
S
W
SC
DECK TYPES

Standard Bar



USE WITH
S
W
SC
DECK TYPES

Heavy Duty Bar



USE WITH
LC
G
CWF
DECK TYPES

Lite-Deck Batten Bar



USE WITH
S
W
SC
DECK TYPES

Polymer Batten Bar

PHYSICAL DATA* & ORDERING INFORMATION

| PRODUCT | CAT. NO. | WIDTH IN (MM) | THICKNESS | HOLE IN (MM) | SPACING (O.C.) IN (MM) | WEIGHT LBS (KG) |
|----------------------|-------------|---------------|-----------------|--------------------|------------------------|-----------------|
| STANDARD BAR | BAT18-6CSH | 1 (25) | 18 Ga. (1.3 mm) | ¼ (6) countersunk | 6 (150) | 80 (36.32) |
| | BAT18-12CSH | | | | 12 (300) | |
| HEAVY DUTY BAR | BAT16-6FH | 1 (25) | 16 Ga. (1.6 mm) | ¼ (6) | 6 (150) | 103 (46.76) |
| LITE-DECK BATTEN BAR | BAT18-6LD | 1 (25) | 18 Ga. (1.3 mm) | ½ (13) countersunk | 6 (150) | 80 (36.32) |
| | BAT18-12LD | | | | 12 (300) | |
| POLYMER BATTEN BAR | 6817910 | ¾ (19) | ½" (1.2 mm) | ¼ (6) | 3 (75) | 8 (3.63) |
| | 6341910 | 1 (25) | | | | 10 (4.54) |

*All sizes are nominal.

KEY:

- S** Steel
- W** Wood
- G** Gypsum
- P** Purlins
- SC** Structural Concrete
- LC** Lightweight Concrete
- LWIC** Lightweight Insulating Concrete
- CWF** Cementitious Wood Fiber



ROOFING PRODUCTS

153 BOWLES ROAD, AGAWAM, MA 01001 USA
800-633-3800 413-789-0252 OMGROOFING.COM

Copyright © 2018 OMG, Inc. All rights reserved.

Superior productivity.
Superior performance.

