



OverFlow Roof Drain Attachment

PRODUCT DATA SPECIFICATIONS

PRODUCT DESCRIPTION

The **OMG OverFlow** accessory is a spun aluminum round drain attachment. The product is designed to be used with all OlyFlow® retrofit and new connection drains that are supplied with a clamping ring assembly. The purpose of the overflow drain assembly is to provide additional water drainage if necessary, when water level on the roof exceeds 2 inches or 4 inches depending on local code.

FEATURES & BENEFITS

- Constructed of .050-in. spun aluminum.
- Provides additional drainage when water level exceeds 2 inches or 4 inches depending on local code.
- Simple and easy to install.

Overflow is compatible with OlyFlow drains with a clamping ring including SpeedTite, and Hercules Plus.

ORDERING INFORMATION

CATEGORY NO.	DESCRIPTION	HEIGHT IN.	PKG QTY	DIMENSIONAL WEIGHT LBS
OVFLOW2-10	OverFlow	2	1	1
OVFLOW4-10	OverFlow	4	1	1



OverFlow 2"



OverFlow 4"

PHYSICAL DATA

The data below is constant for each OMG OverFlow.

OVERFLOW

- 2" Height
- 4" Height
- MATERIAL: .050" aluminum



ROOFING PRODUCTS

153 BOWLES ROAD, AGAWAM, MA 01001 USA
800-633-3800 413-789-0252 OMGROOFING.COM

OlyFlow® is a trademark of OMG Building Products LLC. Copyright © 2025 OMG Building Products LLC. All rights reserved.

Superior productivity.
Superior performance.

